MIRAI

experience the future

DML-517N100

17” / 43 cm LCD MONITOR

1280 x1024

TCO Development TCO'03 DISPLAYS www.tcodevelopment.com

8 ms Ultra Fast

MIRAI
experience the future

DML-517N100
17” / 43 cm LCD MONITOR

Screen Size	337.9 (H) x 270.34 (V)
Driver Element	a-si TFT Active Matrix
Aspect Ratio	4 : 3
Pixel Pitch	0.264 (H) x 0.264 (V)mm
Panel Resolution	1280 x 1024
Pixel Arrangement	RGB Vertical Stripe
Tran Missive Mode	Normally White
Brightness (typ.)	300 cd/m^2
Contrast Ratio (typ.)	400 : 1
Response Time (typ.)	8 ms (Tr:2 + Tf:6)
Viewing Angles (typ.)	150^0 (H) / 130^0 (V)
Display Color	16.2M
Horizontal Sync.	Positive / Negative
Vertical Sync.	Positive / Negative
Input Connector	D-Sub mini 15 pins
Auto Adjust	Clock, Phase, H-Position, V-Position
Screen Scaling	VGA/SVGA/XGA/SXGA Full Screen Display
Power Management	VESA DPMS, ENERGY STAR® Compliance
COLOUR Adjustment	User, 6500K, 7500K, 9300K
Power Input	AC 100-240 V (Worldwide)
Input frequency	50-60Hz
Operation Mode	45W
Power Saving Sleep Mode	2W @230VAC 50Hz
Power Saving OFF Mode	1W @230VAC 50Hz
Screen Recovery Time	Within 3 sec
Input System	RGB Seperate
Video Frequency Bandwidth	135 MHz dot clock
Tilt Angle	20^0 (Upward) / 0^0(Downward)
Dimension	378 (W) x 404 (H) x 190 (D) mm
Weight	3.8 Kg

Jupiterstraat 106, 2132 HE Hoofddorp, The Netherlands
TEL +31 (0)23 - 567 10 56 FAX +31 (0)23 - 567 10 67
info@nl-mirai.com

www.mirai.eu